

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
21 July 2005 (21.07.2005)

PCT

(10) International Publication Number  
**WO 2005/066020 A1**

(51) International Patent Classification<sup>7</sup>: **B64C 29/00**

(21) International Application Number:  
PCT/GB2004/005449

(22) International Filing Date:  
23 December 2004 (23.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0400335.6 8 January 2004 (08.01.2004) GB

(71) Applicant and

(72) Inventor: **BURRAGE, Robert, Graham** [GB/GB]; 1 The Chestnuts, Abingdom, Oxfordshire OX14 3YN (GB).

(74) Agents: **MOIR, Michael, Christopher** et al.; Mathys & Squire, 120 Holborn, London EC1N 2SQ (GB).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: TILT-ROTOR AIRCRAFT



(57) Abstract: A tilt-rotor aircraft (1) comprising a pair of contra-rotating co-axial tiltable rotors (11) on the longitudinal centre line of the aircraft. The rotors (11) may be tiltable sequentially and independently. They may be moveable between a lift position and a flight position in front of or behind the fuselage (19).

WO 2005/066020 A1